# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: Premium Living

Supplier's address: -

#### Model identifier: 82270879

### Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |
|-------------------------------|------|---------------------------------|------|--|--|
| Light source cap-type         | LED  |                                 |      |  |  |
| (or other electric interface) |      |                                 |      |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | Nein |  |  |
| Colour-tuneable light source: | Nein | Envelope:                       | -    |  |  |
| High luminance light source:  | Nein |                                 |      |  |  |
| Anti-glare shield:            | Nein | Dimmable:                       | Yes  |  |  |
| Product parameters            |      |                                 |      |  |  |

|                                      |  | Flouuct para            | ineters   |              |  |  |
|--------------------------------------|--|-------------------------|---|--------------|--|--|
| Parameter                            |  | Value                   | Parameter   | Value        |  |  |
| General product parameters:          |  |                         |   |              |  |  |
| 0,                                   | nption in on-<br>100 h), rounded<br>st integer                             | 7                       | Energy efficiency<br>class  | F            |  |  |
| indicating if it r<br>in a sphere (3 | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 650 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 30006500     |  |  |
| On-mode p<br>expressed in W          | oower (P <sub>on</sub> ),  | 6,6                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| for CLS, expres                      | dby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal           | -                       | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 82           |  |  |
| Outer<br>dimensions<br>without       | Height   | 1                       | Spectral power  | See image    |  |  |
|                                      | Width  | 233                     | distribution in the   | in last page |  |  |
|                                      | Depth  | 43                      |   | Seite 1 / 3  |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|--|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)            | -     |  |  |  |
|  |      | Chromaticity                            | 0,436 |  |  |  |
|  |      | coordinates (x and y)                   | 0,402 |  |  |  |
| Parameters for LED and OLED light sources:   |      |   |       |  |  |  |
| R9 colour rendering index value  | 3    | Survival factor                         | 1,00  |  |  |  |
| the lumen maintenance factor   | 0,96 |   |       |  |  |  |
| (a)  |      |   |       |  |  |  |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

## Spectrum

