## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Modern Living

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271398-02

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	4	Energy efficiency class	F		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	320 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	3,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
( $P_{net}$ ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84		
Outer dimen-	Height	50	Spectral power dis-	See image		
sions without	Width	15	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	15	range 250 nm to 800 nm, at full-load	Dage 1 /		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	24			
		Chromaticity coordi- nates (x and y)	0,437 0,395			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	18	Survival factor	1,00			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,96	Colour consistency in McAdam ellipses	3			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)<sub>'-'</sub> : not applicable;

(b)'\_-' : not applicable;

