Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 81810541

Τv	pe	of	light	soui	ce:
. ,	P-	•			···

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED SMD				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					

		1 Todact parai				
Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 00 h), rounded st integer	5	Energy efficiency class	Е		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	580 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 4 000 or 6 000		
On-mode pow pressed in W	ver (P _{on}), ex-	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimen-	Height	18	Spectral power dis-	See image		
sions without	Width	12	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	50	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,366 0,367			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	5	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,2	Stroboscopic effect metric (SVM)	0,2			

(a)'-': not applicable; (b)'-': not applicable;

