## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Luca Bessoni

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

## Model identifier: 63600023

## Type of light source:

| Lighting technology used:     | LED       | Non-directional or directional: | NDLS |
|-------------------------------|-----------|---------------------------------|------|
| Light source cap-type         | DC 24V 1A |                                 |      |
| (or other electric interface) |           |                                 |      |
| Mains or non-mains:           | NMLS      | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No        | Envelope:                       | -    |
| High luminance light source:  | No        |                                 |      |
| Anti-glare shield:            | No        | Dimmable:                       | Yes  |
|                               |           |                                 |      |

| mode (kWh/1000 h), rounded<br>up to the nearest integerclassUseful luminous flux (фuse),<br>indicating if it refers to the flux<br>in a sphere (360°), in a wide<br>cone (120°) or in a narrow cone<br>(90°)2 700 in<br>Sphere (360°)Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be setOn-mode<br>power (Pon),<br>expressed in W24,0Standby power (Psb),<br>expressed in W<br>and rounded to the second decimal0Networked standby power (Pnet)<br>for CLS, expressed in W and<br>rounded to the second decimal-Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be3               | Product parameters                                       |                                    |       |  |              |  |  |
|--|--|------------------------------------|-------|--|--------------|--|--|
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer24Energy efficiency<br>classUseful luminous flux (\$use),<br>indicating if it refers to the flux<br>in a sphere (360°), in a wide<br>cone (120°) or in a narrow cone<br>(90°)2 700 in<br>Sphere (360°)Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set3On-mode power (Pon),<br>expressed in W24,0Standby power (Psb),<br>expressed in W0Networked standby power (Pnet)<br>for CLS, expressed in W and<br>rounded to the second decimal-Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be- | Parameter  |                                    | Value | Parameter  | Value        |  |  |
| mode (kWh/1000 h), rounded<br>up to the nearest integerclassUseful luminous flux (\$\phiuse),<br>indicating if it refers to the flux<br>in a sphere (360°), in a wide<br>cone (120°) or in a narrow cone<br>(90°)2 700 in<br>Sphere (360°)Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be setOn-mode<br>expressed in W24,0Standby power (P_{sb}),<br>expressed in W0Networked standby power (P_{net})<br>for CLS, expressed in W and<br>rounded to the second decimal-Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be3   | General product parameters:                              |                                    |       |  |              |  |  |
| indicating if it refers to the flux<br>in a sphere (360°), in a wide<br>cone (120°) or in a narrow cone<br>(90°)Sphere (360°)temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be setOn-mode<br>power (Pon),<br>expressed in W24,0Standby power (Psb),<br>expressed in W0Networked standby power (Pnet)<br>for CLS, expressed in W and<br>rounded to the second decimal-Colour<br>rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be-  | mode (kWh/10   | 000 h), rounded                    | 24    |  | F            |  |  |
| expressed in W expressed in W   expressed in W expressed in W   and rounded to the second decimal second decimal   Networked standby power (P <sub>net</sub> ) -   for CLS, expressed in W and rounded to the second decimal index, rounded to the nearest integer, or the range of CRI-values that can be   | indicating if it r<br>in a sphere (3<br>cone (120º) or i | refers to the flux 60°), in a wide |       | temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that | 3 000        |  |  |
| for CLS, expressed in W and<br>rounded to the second decimal index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be   | •  |                                    | 24,0  | expressed in W and rounded to the  | 0,00         |  |  |
|  | for CLS, expre   | essed in W and                     | _     | index, rounded to<br>the nearest integer,<br>or the range of CRI-  | 80           |  |  |
| Outer Height 1 Spectral power See  | Outer  | Height                             | 1     | Spectral power   | See image    |  |  |
| <b>Under</b>   | dimensions<br>without                                    | Width                              | 8     | distribution in the  | in last page |  |  |
| without Depth 1 152  |  | Depth                              | 1 152 |  |              |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |            | range 250 nm to 800<br>nm, at full-load |       |
|--|------------|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | -          | If yes, equivalent power (W)            | -     |
|  |            | Chromaticity                            | 0,440 |
|  |            | coordinates (x and y)                   | 0,403 |
| Parameters for LED and OLED ligh   | t sources: |   |       |
| R9 colour rendering index value  | 0          | Survival factor                         | 0,90  |
| the lumen maintenance factor   | 0,96       |   |       |
| (a)  |            |   |       |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

