Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Bessagi Home
--------------------------------	--------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271261

Τv	pe	of	light	soui	ce:
. ,	P-	•			···

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED Module				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on-	35	Energy efficiency	Е		

Parameter		Value	Parameter	Value
		General product p	arameters:	
	nption in on- 00 h), rounded st integer	35	Energy efficiency class	Е
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 200 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500
On-mode power (P _{on}), expressed in W		35,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate con-	Height Width Depth	1 3 713 8	Spectral power distribution in the range 250 nm to 800	See image in last page
trol gear, light- ing control	σεριπ	J	nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equiva	lent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity coordinates (x and y)	0,434 0,400
Parameters for	LED and OLED lig	ht sources:		
R9 colour rende	ring index value	4	Survival factor	1,00
the lumen main	tenance factor	0,96		
Parameters for LED and OLED mains light sources:				
displacement fa	ctor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5
replaces a flu	LED light source uorescent light integrated balar wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (F	Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1

(a)'-': not applicable; (b)'-': not applicable;

