Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's | name o | or trade mark: | Modern Living |
|------------|--------|----------------|---------------|
|------------|--------|----------------|---------------|

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271398-01

| Type of light sour | Type | of li | ght | sourc | e: |
|--------------------|------|-------|-----|-------|----|
|--------------------|------|-------|-----|-------|----|

| Lighting technology used: | LED | Non-directional or directional: | NDLS | |
|-------------------------------|----------|---------------------------------|------|--|
| Light source cap-type | LED Lamp | | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No | |
| Colour-tuneable light source: | No | Envelope: | - | |
| High luminance light source: | No | | | |
| Anti-glare shield: | No | Dimmable: | No | |
| Product parameters | | | | |

| Froduct parameters | | | | |
|--|---|-------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| General product parameters: | | | | |
| | mption in on- 00 h), rounded st integer | 5 | Energy efficiency class | E |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 550 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode power (P _{on}), expressed in W | | 4,5 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 57 | Spectral power dis- | See image |
| sions without | Width | 15 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 15 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- | | | | |
|---|-------------|--|-------|--|
| trol parts, if any (millime-tre) | | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | |
| | | Chromaticity coordi- | 0,439 | |
| | | nates (x and y) | 0,401 | |
| Parameters for LED and OLED lig | ht sources: | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | |
| the lumen maintenance factor | 0,96 | | | |
| Parameters for LED and OLED mains light sources: | | | | |
| displacement factor (cos φ1) | 0,90 | Colour consistency in McAdam ellipses | 6 | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replace- ment claim (W) | - | |
| Flicker metric (Pst LM) | 0,1 | Stroboscopic effect metric (SVM) | 0,1 | |

(a)'-': not applicable; (b)'-': not applicable;

