## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Luca Bessoni  Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT  Model identifier: 82270988  Type of light source:  Lighting technology used: LED Non-directional or directional:  Light source cap-type LED Module  (or other electric interface)  Mains or non-mains: NMLS Connected light source (CLS):				
Model identifier: 82270988  Type of light source:  Lighting technology used:  Light source cap-type (or other electric interface)  Mains or non-mains:  NMLS  LED  Non-directional or				
Type of light source:  Lighting technology used:  Light source cap-type (or other electric interface)  Mains or non-mains:  LED Non-directional or directional:  NDLS directional:  NDLS Connected light No				
Lighting technology used:  Light source cap-type (or other electric interface)  Mains or non-mains:  LED  Non-directional or directional:  NDLS  LED Module  Connected light  No				
directional:  Light source cap-type (or other electric interface)  Mains or non-mains:  NMLS  Connected light  No				
(or other electric interface)  Mains or non-mains:  NMLS  Connected light  No				
Mains or non-mains: NMLS Connected light No				
Colour-tuneable light source: No Envelope: -				
High luminance light source: No				
Anti-glare shield: No Dimmable: No				
Product parameters				
Parameter Value Parameter Value				
General product parameters:				
Energy consumption in on- 19 Energy efficiency E class up to the nearest integer				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)  Sphere (360°)  Sphere (360°)  Sphere (360°)  Sphere (360°)  Temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set				
On-mode power (Pon), expressed in W and rounded to the second decimal 0,00				
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal  rounded to the second decimal  or the range of CRI-values that can be set				
Outer Height 2 Spectral power See image				
dimensions Width 10 distribution in the in last page				
without Depth 1 212				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity	0,382	
		coordinates (x and y)	0,384	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	2	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

