## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Luca Bessoni

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

## Model identifier: 82271388

## Type of light source:

L'abie a ta des als avec a de			NDLC
Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light source cap-type	LED Module		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neares	00 h), rounded	24	Energy efficiency class	E	
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	2 800 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
(P <sub>net</sub> ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen- sions without separate con-	Height Width	2 200 6	Spectral power dis- tribution in the range 250 nm to 800	See image in last page	
trol gear, light- ing control	Depth	2	nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,437 0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)<sub>'-'</sub> : not applicable;

(b)'\_-' : not applicable;

