Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Premit	um Living
--	-----------

Supplier's address: Importableilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271223

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

ing control

Type of light 30	arcc.			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	o-type	LED Module		
(or other electri	(or other electric interface)			
Mains or non-mains:		MLS	Connected light source (CLS):	Yes
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	24	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	2 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500
On-mode pov pressed in W	ver (P _{on}), ex-	24,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, (tandby power expressed in W the second dec-	0,40	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	2	Spectral power dis-	See image
sions without	Width	10	tribution in the	in last page
separate con- trol gear, light-	Depth	2 600	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime-						
tre)		If was assistated				
Claim of equivalent power ^(a)	_	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,375			
		nates (x and y)	0,368			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	6	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	4			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	t	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,6	Stroboscopic effect metric (SVM)	0,1			

(a)'-': not applicable; (b)'-': not applicable;

