## **Product Information Sheet**

pressed in W

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Modern Living						
Supplier's address: Importabteil	lung, Römerstraße 3	9, 4600 Wels, AT				
Model identifier: 63600025						
Type of light source:						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Connected lead					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
	Product para	meters				
Parameter	Value	Parameter	Value			
	General product p	arameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	25	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500			
On-mode power (P <sub>on</sub> ), ex-	25,0	Standby power (P <sub>sb</sub> ),	0,00			

			ond decimal	
Networked st (P <sub>net</sub> ) for CLS, e and rounded to imal	•	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	2	Spectral power dis-	See image
sions without	Width	16	tribution in the	in last page
separate con- trol gear, light- ing control	ol gear, light-	range 250 nm to 800 nm, at full-load		
'	,	,	•	Page

expressed in W and rounded to the sec-

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,463			
		nates (x and y)	0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;

