Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name o	or trade mark:	Modern Living
------------	--------	----------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271516

Type	of	light	source:
-,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		0	

Product parameters			
Anti-glare shield:	No	Dimmable:	Yes
High luminance light source:	No		
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	NMLS	Connected light source (CLS):	No
(or other electric interface)			
Light source cap-type	LED Module		
Lighting technology used:	LED	Non-directional or directional:	NDLS
Lighting technology used:	LED	Non-directional or	NDLS

Troduct parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consur mode (kWh/10 up to the neares	00 h), rounded	10	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		890 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006000
On-mode power (P _{on}), expressed in W		9,4	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,30
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90
Outer dimensions without separate control gear, lighting control	Height	1	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image
	Width	320		in last page
	Depth	20		

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,440
		nates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value	60	Survival factor	1,00
the lumen maintenance factor	0,95		

(a)'-': not applicable; (b)'-': not applicable;

