## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or t	ade mark: N	Modern Living
----------------------	-------------	---------------

Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT

Model identifier: 82271438

Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	LED Module			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				

## Product parameters

Parameter		Value	Parameter	Value		
	General product parameters:					
٠,	nption in on- 00 h), rounded st integer	12	Energy efficiency class	F		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	12,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimensions without separate control gear, lighting control	Height	6	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image		
	Width	880		in last page		
	Depth	16				

parts and non- lighting con- trol parts, if any (millime-					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,443 0,409		
Parameters for LED and OLED lig	ht sources:				
R9 colour rendering index value	2	Survival factor	1,00		
the lumen maintenance factor	0,94				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1		

(a)'-': not applicable; (b)'-': not applicable;

