## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Luca Bessoni						
						Supplier's address: Importabteilung, Römerstraße 39, 4600 Wels, AT
Model identifie	r: 82270905					
Type of light so	urce:					
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap-type		LED Module				
(or other electri	ic interface)					
Mains or non-m	nains:	MLS	Connected light source (CLS):	Yes		
Colour-tuneable	e light source:	Yes	Envelope:	-		
High luminance		No				
Anti-glare shield:		No	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		24	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), expressed in W		24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,42		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,44	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	280	Spectral power	See image		
dimensions without	Width	280	distribution in the	in last page		
vvitilout	Depth	1				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,439			
		coordinates (x and y)	0,405			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	5	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	1			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	0,1	Stroboscopic effect metric (SVM)	0,1			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

